





- Recommended working pressure: 0.5 kgf/cm²
- Flowrate tolerance: ± 10% @ 0.5 ± 0.1 kgf/cm²

Features


- Used for liquid stirring under the liquid surface. Specially designed nozzle that creates a stirring and circulating effect. This nozzle can mix chemicals, direct the suspended substances to a filter and prevent precipitation.
- Energy-efficiency of liquid stirring: the eductor nozzles are designed to suck and spray liquid through the amplified nozzle tube to increase liquid flow rate up to 4 times which provides more efficient stirring than aeration or robot arms

(Quantity supplied+Intake=Total Flow).

Single piece structure and hand installable without any tools.

Applications

- Cleaning: scrubber, off-gas treatment, etc.
- Cooling: cooling tower, etc.
- Dispersion: firefighting.



Material	Serise	Unit	(mm)	Thread	Weight (g)		
ivialeriai		А	В	Туре	S316	FRPP	
Metal	3/8ED	116	54	3/8M	274	-	
Plastic	3/8ED	116	54	3/8M	-	34	
Plastic	3/4ED	159	74	3/4M	-	84.6	

Appearance dimensions may vary depending on model, material. Please ask for details.

Material

- Strengthened Pipe Fiberglass PP
- Stainless 316 (Only 3/8")

How to p	How to pleace an order for LORRIC nozzles?									
Example	3/8	BSPT	ED	152	-	FRPP				
	1	<u></u>	1	1	1	<u></u>				
	Thread Type	Thread Size	Capacity Code	Capacity Code	Spray Angle	Material	Standard Pressure: Column in red.			

Thread	Capacity Code	Magnification	Definition of flow	Capacity at Pressure									
Size				0.1 kgf/cm²	0.25 kgf/cm²	0.5 kgf/cm²	0.75 kgf/cm²	1 kgf/cm²	1.5 kgf/cm²	2 kgf/cm²	3 kgf/cm²	4 kgf/cm²	
		- 5.0	Quantity supplied	5.59	8.84	12.50	15.31	17.68	21.65	25.00	30.62	35.36	
	63		Intake	22.36	35.36	50.01	61.25	70.72	86.61	100.01	122.49	141.44	
3/8			Total Flow	27.95	44.20	62.51	76.56	88.40	108.27	125.02	153.11	176.80	
3/8			Quantity supplied	10.87	17.18	24.30	29.76	34.36	42.08	48.59	59.51	68.72	
	152		Intake	43.46	68.72	97.18	119.03	137.44	168.33	194.37	238.05	274.88	
			Total Flow	54.33	85.90	121.48	148.78	171.80	210.41	242.96	297.57	343.60	
	-	5.0	Quantity supplied	19.57	30.94	43.75	53.58	61.87	75.77	87.50	107.16	123.74	
3/4			Intake	78.26	123.74	174.99	214.32	247.48	303.10	349.99	428.65	494.96	
			Total Flow	97.83	154.68	218.74	267.90	309.35	378.87	437.49	535.81	618.70	

^{*} For MPa / bar / psi units, please refer to LORRIC.com.